MATERIAL SAFETY DATA SHEET PRINTING INKS AND RELATED MATERIALS

#020

HMIS HAZARD RATING
HEALTH......1
FLAMMABILITY.....1
PHYSICAL HAZARD....0

Date prepared \_\_\_\_5/13/2009 \_\_\_\_ prepared by \_\_\_\_Doug Chesley \_\_\_

**Section I** 

PRODUCT CLASS: Offset Non-Oxidizing Ink
Trade Name: Printek and or Rubberbase

MANUFACTURERS NAME & ADDRESS: Graphic Ink Co. 3135 W. DIRECTORS ROW S.L.C., UT.

EMERGENCY PHONE NUMBER: (801) 972-6142

**Section II - HAZARDOUS INGREDIENTS** 

Ingredient: / Hazard Data:

NO HAZARDOUS INGREDIENTS BY CURRENT OSHA STANDAR **Essentially a Non-Hazardous Mixture** 

**Section III - PHYSICAL DATA** 

Boiling range: 495-548 F Percent volatile Wt.: 5-10%

Vapor Density vs. Air: HEAVIER Liquid Density vs. Water: HEAVIER Appearance: COLORED PASTE Type of Odor: RESINOUS VARNISH

**Evaporation Rate vs. Butyl Acetone: SLOWER** 

Solubility in Water: INSOLUBLE

Section IV - FIRE & EXPLOSION DATA

Flammability Classification: COMBUSTIBLE OSHA: 1118 DOT: NOT REGULATED

Flashpoint: 256 F (test method-ASTM 0-93) LEL-NO DATA

**Extinguishing Media:** 

FOAM-(X) ALCOHOL FOAM-() CO2-(X) DRY CHEMICAL-(X WATER FOG-()

Unusual Fire Explosion Hazards: MAY GENERATE DENSE SMOKE WHEN BURNING.

Special Firefighting procedures: USE SELF CONTAINED BREATHING APPARATUS TO AVOID POTENTIALLY HARMFUL OR IRRITATING FUMES.

**Section V - HEALTH HAZARD DATA** 

Effects of Over Exposure: EYE CONTACT WILL CAUSE IRRITATION. PROLONGED SKIN

**CONTACT MAY CAUSE IRRITATION.** 

Medical conditions aggravated by exposure: NONE KNOWN.

Primary Route (s) or Entry: DERMAL - (X) INHALATION-(X)

**Emergency & First Aid Procedures:** 

EYE CONTACT--FLUSH EYES FOR 15 MINUTES WITH WATER. SEEK MEDICAL ATTENTION, SKIN CONTACT--WASH EFFECTED AREAS WITH SOAP & WATER. REMOVE CONTAMINATED

CLOTHING & LAUNDER BEFORE WEARING. INHALATION--REMOVE TO FRESH AIR.

INGESTION--DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.

## **OFFSET QUICKSET OXIDIZING INK**

PAGE 2

#### **Section VI - REACTIVITY DATA**

**Product Stability: STABLE** 

Conditions To Avoid: EXTREME HEAT. STRONG OXIDIZING AGENTS.

# Section VII - SPILL OR LEAK PROCEDURES

Procedure if Material is Spilled or Released: SCRAPE UP THE BULK WITH INK OR

PUTTY KNIFE. WASH AREA WITH DETERGENT AND WATER.

Waste Disposal Method: INCINERATION IS THE PREFERRED METHOD < BUT ONLY BY

LICENSED HAZARDOUS WASTE DISPOSAL COMPANIES.

## Section VIII - SPECIAL PROTECTION INFORMATION

Ventilation: GENERAL PLANT VENTILATION

Protection Gloves: SYNTHETIC RUBBER GLOVES MAY BE WORN SUBJECT TO EXPOSURE.

**Respiratory Protection: NOT REQUIRED** 

Eye Protection: GOGGLES OR FACE SHIELD MAY BE WORN.

Other Protective Equipment: PROTECTIVE OUTERWEAR IS RECOMMENDED.

## **Section IX - SPECIAL PRECAUTIONS**

Handling & Storage: STORE UPRIGHT, IN SEALED METAL CONTAINERS AWAY FROM HEAT OR OPEN FLAMES. CLEAN UP SPILLS PROMPTLY, TO AVOID SLIPPING OR TRACKING.

Other Precautions: DO NOT TRANSFER INTO UNMARKED CONTAINERS.

The information and recommendations contained herein are proprietary, and are furnished solely for use by our customers. While believed to be true and accurate, they are offered solely for consideration, investigation and verification. NO GUARANTEE or WARRANTY of any kind is expressed or implied by Graphic Ink Co. with respect to this data. The applicability of Local, State, and Federal laws and regulations to this information must be determined by user.